





# SGA™ Receiver Sling Mount

for Remington® 870




- ⚠ **WARNING:** BEFORE STARTING, MAKE SURE THE WEAPON IS UNLOADED, THE CHAMBER IS EMPTY, AND THE SAFETY ENGAGED.
- ⚠ **CAUTION:** PLEASE READ ALL INSTRUCTIONS BEFORE PROCEEDING. COMPONENTS UNDER SPRING PRESSURE MAY EJECT FORCEFULLY AND COULD CAUSE INJURY.
- ⚠ **WARNING:** OBSERVE SAFE FIREARM HANDLING PRACTICES AT ALL TIMES. FAILURE TO DO SO MAY RESULT IN SERIOUS BODILY INJURY OR DEATH. MAGPUL INDUSTRIES SHALL NOT BE RESPONSIBLE FOR INJURY, DEATH OR PROPERTY DAMAGE RESULTING FROM FAULTY INSTALLATION, MISUSE, ILLEGAL USE, OR MODIFICATION OF THIS PRODUCT.

## INSTALLATION INSTRUCTIONS




### STEP 1: STOCK REMOVAL

Uninstall SGA stock and adapter plate per factory instructions by removing rubber thumb strip access cover and screw with hex key provided with stock.



### STEP 2: SLING POINT INSTALLATION


Position Receiver Sling Mount as depicted with Sling Loop on desired side of receiver and reinstall stock. Receiver Sling Mount can be mounted with Sling Loop on the right for left-handed users.



### STEP 3: REINSTALL STOCK

Replace screw, tighten, and reinstall rubber thumb strip to complete stock installation.

**Note:** Take care not to over-tighten screw. Over tightening may result in damage to the sling mount, stock, or firearm receiver.



### STEP 4: VERIFY INSTALL

Perform final inspection including function test to verify correct installation.

**Note:** Always test fire your weapon before using it in an operational environment.